

# APEX Inflatable Roll up A-24

## Standard Equipment

- 2 Oars
- 2 Oarlocks
- 2 Oarlocks base
- 2 Oar rests
- 1 Bench Seat
- 2 Seat brackets
- 2 Life lines
- 3 Inflation valve
- 1 Foot pump
- 1 Repair kit
- 1 Front handles
- 2 Side cleat hanc
- 1 Light gray rais
- 2 Towing rings
- 1 Deck-wood panels
- 1 Inflatable Keel
- 1 Hull drain with plug
- 2 Transom engine plates
- 1 Carry Bag

## Dimensions

- Length ft (m) 8'0" (2.44)
- Beam ft (m) 4'6" (1.37)
- Int. Length ft (m) 5'3" (1.60)
- Int. Beam ft (m) 2'0" (0.61)
- Tube Diameter Inch (cm) 15" (38)
- Air Chambers 2+1
- Persons 4
- Keel Inflatable
- Payload lbs (kg) 860(391)
- Weight lbs (kg) RI=66(30) RIL=56(25) WI=69(31)
- Rec. H/P (kw) 4(3)
- Max. H/P (kw) 6(4.5)
- Shaft Length S/15"
- Stowed Length ft (m) 3'0"(0.91)
- Stowed Width ft (m) 2'0" (0.61)
- Stowed Height ft (m) 1'0" (0.30)

